

Portable, Hot Water Power, Pressure Washer

Easy-Handling for Commercial Applications









LIBERTY HDS P/PE CAGE



Outstanding on all terrains.

Built on a rugged 1-1/4" powder coated steel frame, these compact gas roll cage models are designed for construction sites, farms and factories. The different models deliver hot water cleaning of up to 3500 PSI. Each features a Kärcher pump with limited 7-year warranty, industrial-grade motor and flat-free tires. All are certified to UL and CSA safety standards.





1 Powerful and durable

- Industrial-grade Honda and Robin engines with two-year warranty; two models with electric-start standard.
- Efficient burner with transformer for years of reliable and affordable operation.
- Industrial-grade, tri-plunger, oil-bath, direct- drive, Kärcher pump with 7-year warranty.
- 50 ft. of durable, wire braid hose rated for 3000 or 4500 PSI; with hose guard for burst protection.
- Heavy-gauge 11/4" steel frame with powder coat finish for all-weather protection.
- Power platform cushioned on 4 vibration isolators for smoother operation and long-life protection to frame and components.
- Insulated Schedule 80 heating coil is made of 1/2-inch steel pipe and cold-rolled; comes standard with stainless steel coil wrap and 5-year warranty.

2 Smart features

- Four conveniently mounted, quick-couple spray nozzles for varying fan spray.
- Safety relief valve attached to discharge side for protection against excess pressure build up.
- Rust-free, 6-gallon polyethylene diesel fuel tank for hours of operation without interruption.
- Insulated, high-pressure trigger gun for hours of fatigue-free cleaning.
- Water resistant control box with burner on/off switch, adjustable thermostat and hour meter.
- Thermal pump saver valve protects against hot-water damage by venting recirculated water.
- Insulated, dual-lance variable pressure wand with quick-couple connectors for easy attachment of high-pressure spray nozzles.

2016 · p/n 9.800-131.0 · Rights to technical modifications reserved.

Technical data and equipment.

Technical Data										
Model	Part No.	GPM	PSI	cc	Engine	Start	Pump	Burner	Weight (lbs.)	Dimensions (L x W x H) inches
HDS 2.8/25 P Cage	1.575-555.0	2.7	2400	211	Subaru EX21	Recoil	Kärcher KG	12V DC	404	50 x 40 x 50
HDS 2.6/30 P Cage	1.575-550.0	2.6	3000	270	Honda GX270	Recoil	Kärcher KG	12V DC	500	39 x 28 x 42
HDS 3.5/30 P Cage	1.575-551.0	3.5	3000	337	Honda GX340	Recoil	Kärcher KS	12V DC	550	46 x 28 x 44
HDS 3.5/30 Pe Cage	1.575-552.0	3.5	3000	337	Honda GX340	Electric	Kärcher KS	12V DC	560	46 x 28 x 44
HDS 3.5/35 Pe Cage	1.575-553.0	3.5	3500	389	Honda GX390	Electric	Kärcher KS	12V DC	595	46 x 28 x 44

Options (field installed)		
Product	Order No.	Description
100' EZEE hose reel kit	9.801-024.0	100' EZEE hose reel kit (hose not included)
100' Pivot Hose Reel Kit	9.804-570.0	100' pivot hose reel kit (hose not included)