TULE SERIES HDS 3.5/40 GE MT



Towable and maneuverable hot water pressure washer.

Ready to pick up and go at a moments notice, Kärcher's Tule Series HDS 3.5/40 Ge MT hot water pressure washer trailer provides the necessary cleaning power on virtually any job site which has a water source. Simply unhitch the Tule Series HDS 3.5/40 Ge MT and take the cleaning power where you need it most. The Tule Series trailer features a reliable Honda engine, 8 gallon diesel fuel tank, electric start with manual start backup and much more.

U.S. Design Patent No. 9,724,734 B2



















1 Smart design

- Reliable Honda GX engine
- 8-gallon diesel fuel tank
- Manual parking brake
- Adjustable bracket and multiple hitch configurations for various vehicle heights
- Adjustable thermostat for regulating water temperature
- 2-inch Ball Coupler for quick and easy hook up of trailer
- EASY!Force trigger gun with cruise control like technology uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

2 Ease of use

- Electric start with manual start backup
- Controls are located on the curb side of the trailer
- Easy to use only 2 switches to operate the entire unit
- 12V Battery included for hot water operation

3 Mobile

- Highway rated 16" pneumatic tires
- Compact design and easy towing for on-site applications, manueverability and storage
- Lift handle and swing away tongue for easier hook up of the trailer and storage

Technical data and equipment

Features

■ Honda GX 390 engine■ 8 gallon diesel fuel tank

■ Adjustable thermostat for water temperature regulation

■ Electric start with manual start backup

Technical Data

Model	Part No.	GPM	PSI	Drive	Burner	Engine	Start	Pump	Ship weight (lbs.)	Dimensions (L x W x H) inches
HDS 3.5/40 Ge MT	1.103-844.0	3.5	4000	Direct	12V / DC	Honda GX390	Electric	Kärcher KS	1000	100 x 45 x 75

Standard Accessories	
Order No.	Description
8.756-481.0	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.
9.802-225.0	3 - 5 GPM Chemical Injector Kit
8.754-990.0	12V Battery (required for hot water operation)
8.924-366.0	2-inch ball coupler
8.711-293.0	Zinc plated variable pressure lance

Options (factory installed)

Order No.	Description
8.924-367.0	2-5/16-inch Ball Coupler
8.924-667.0	Lifting Kit
8.924-370.0	LED Lights
8.924-700.0	2-inch Collar Lock Coupler

Options (field installed)

Order No.	Description
8.750-682.0	Hose Reel Fixed 100', 5000 PSI, 325° F, equipped for 3/8" hose
8.925-255.0	Hose Reel Bracket (Mount Kit)



