

Electric-Powered, Diesel-Heated, Pressure Washer

Portable Hot Water Power with Roll Cage



Hot Water | Electric Powered | Diesel Heated



Liberty HDS Cage

Built on a rugged 1-1/4" powder coated steel frame, these compact electric roll cage models are designed for construction sites, farms and factories where electricity is available. The three models deliver hot water cleaning of up to 2000 PSI using 120V or 230V/1ph. Each features a Kärcher direct-drive crankcase-style pump with 7-year warranty, industrial-grade motor and 1/2" Schedule 80 heating coil with stainless steel wrap. All are certified to UL and CSA standards.

Powerful and durable

- 120V 1725 RPM or 230V 3450 RPM industrial-grade Baldor motors provide reliable power to the pump.
- Industrial-grade, tri-plunger, oil-bath, direct-drive, Kärcher pump with 7-year warranty.
- 50 ft. of durable, wire braid hose rated for 3000 PSI and with hose guard for burst.
- Safety relief valve attached to discharge side for protection against excess pressure build up.
- Insulated Schedule 80 heating coil is made of 1/2-inch steel pipe and cold-rolled; comes standard with stainless steel coil wrap and 5-year warranty.
- Thermal pump saver valve protects against hot-water damage by venting recirculated water.

Smart features

- Efficient burner with transformer for years of reliable and affordable operation.
- Easy-to-attach downstream detergent injection with quick couplers and brass soap nozzle.
- Fuel filter/water separator ensures pure fuel supply.
- Insulated, high-pressure trigger gun for hours of fatigue-free cleaning.

Outstanding mobility

- Compact 1 1/4" powder-coated steel roll-cage frame protects machine components and is highly maneuverable.
- 13-inch tubed pneumatic tires for easy handling on all terrains.

LANDA® Northwest

11811 NE Marx Street, Portland, OR 97220
P.O. Box 20037, Portland, OR 97294-0037

(503) 255-6508 • (800) 247-8103 • Fax (503) 255-4717 landanw.com

Technical Data and Equipment

HDS 2.0/10 Ed Cage

HDS 1.9/15 Ed Cage

HDS 3.5/20 Ea Cage

- Rugged steel chassis & roll cage
- Available in 120V and 230V
- Kärcher's Direct-drive crankcase style pumps
- Stainless steel coil wrap standard
- Oil-water separator and hour meter
- 1725 RPM motors on 1.5-2 HP models



Technical Data

GPM		2.1	1.9	3.5
PSI		1000	1500	2000
HP		1.5	2	5
Electrical		120V / 1ph	120V / 1ph	230V / 1ph
Pump		Kärcher KE	Kärcher KE	Kärcher KE
Amps		15	20	22
Ship Weight	lbs.	480	480	500
Dimensions (L x W x H)	inches	39 x 27 x 44	39 x 27 x 44	39 x 27 x 44
Order No.		1.575-511.0	1.575-512.0	1.575-513.0

Options (field installed)

9.801-024.0	100' EZEE hose reel kit (hose not included)
9.804-570.0	100' Pivot hose reel kit (hose not included)

LANDA® Northwest

11811 NE Marx Street, Portland, OR 97220
P.O. Box 20037, Portland, OR 97294-0037
(503) 255-6508 • (800) 247-8103 • Fax (503) 255-4717 landanw.com